

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
12 June 2003 (12.06.2003)

PCT

(10) International Publication Number  
WO 03/047541 A1(51) International Patent Classification<sup>7</sup>: A61K 7/13, 7/06

(21) International Application Number: PCT/EP02/12627

(22) International Filing Date:  
12 November 2002 (12.11.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
013101308 4 December 2001 (04.12.2001) EP  
02205789 4 September 2002 (04.09.2002) GB

(71) Applicant (for EP, JP, IL, BR, BZ, CA, CY, GB, GD, GH, GM, HU, IL, KE, LC, LK, LN, MN, MW, NZ, OM, SD, SG, SL, SZ, TT, TZ, UG, VC, ZA, ZM, ZW only): UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ (GB)

(71) Applicant (for AL, AM, AT, AZ, BA, BE, BF, BG, BJ, BR, BY, CF, CG, CH, CI, CM, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, FR, GA, GE, GN, GQ, GR, GW, HR, HU, ID, IS, IT, JP, KG, KP, KR, KZ, LR, LT, LU, LV, MA, MC, MD, MG, MK, ML, MR, MX, MZ, NE, NL, NO, PH, PL, PT, RO, RU, SE, SI, SK, SN, TD, TG, TJ, TM, TN, TR, UA, UG, US, UZ, VC, VN, YU only): UNILEVER NV [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL).

(71) Applicant (for IN only): HINDUSTAN LEVER LIMITED [IN/IN]; Hindustan Lever House, 165/166 Backbay Reclamation, Maharashtra, 400 020 Mumbai (IN).

(72) Inventors: and

(75) Inventors/Applicants (for US only): ARAI, Takeshi

[JP/GB]; Unilever Research Port Sunlight, Quarry Road East, Bebington, Wirral, Merseyside CH63 3JW (GB). BAKER, Mark, Edward, James [GB/GB]; Unilever Research Port Sunlight, Quarry Road East, Bebington, Wirral, Merseyside CH63 3JW (GB). GILES, Colin, Christopher, David [GB/GB]; Unilever Research Port Sunlight, Quarry Road East, Bebington, Wirral, Merseyside CH63 3JW (GB).

(74) Agents: TANSLEY, Sally, Elizabeth et al.; Unilever PLC, Patent Department, Colworth House, Sharnbrook, Bedford, Bedfordshire MK44 1LQ (GB).

(81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: HAIR TREATMENT COMPOSITION COMPRISING COMPOSITE PARTICLES OF CLAY AND CHARGED ORGANIC MOLECULE

(57) Abstract: A hair treatment composition comprising an aqueous dispersion of composite particles, said particles comprising: i) a clay with a net surface charge, and ii) a charged organic molecule comprising at least 6, preferably at least 11, more preferably at least 17 carbon atoms, wherein the charge on the charged organic molecule is opposite to the net surface charge of the clay, said hair treatment composition further comprising one or more suitable hair treatment ingredients.

- 1 -

HAIR TREATMENT COMPOSITION COMPRISING COMPOSITE PARTICLES OF CLAY AND CHARGED  
ORGANIC MOLECULE

TECHNICAL FIELD

5 The present invention relates to hair treatment compositions  
comprising aqueous dispersions of composite particles and  
processes for their preparation. Water based hair treatment  
compositions containing particles according to the  
invention, such as conditioner and shampoo compositions,  
10 provide specific feel benefits to hair.

BACKGROUND OF THE INVENTION

15 The way their hair feels is very important to consumers of  
hair products. Desirable feel characteristics for hair  
include smoothness, softness, slippery feel when wet, ease  
of comb (both in the wet and dry states), no static,  
moisturisation and cleanness.

20 Compositions which provide improved feel to the hair are  
well known in the art and include rinse off products such as  
conditioners, shampoos, shower-gels, lotions and the like.  
These compositions improve feel characteristics of hair by  
depositing one or more of a wide variety of benefit agents,  
25 such as conditioning agents, onto the hair. However, such  
compositions can also lead to the hair looking and feeling  
heavy, greasy, dull and lifeless, due to the presence and/or  
accumulation of benefit and/or deposition agents on the  
surface of the hair. The clean feel of the hair can then be  
30 restored by removing these agents, for example by use of a  
so-called cleansing shampoo. However, the hair can then

- 2 -

feel difficult to comb, harsh and lacks the benefits bestowed by the benefit agents just removed. In particular, such shampooing can leave the hair in a tangled and generally unmanageable state. Once the hair dries, it is often dry, rough, lustreless, or frizzy due to removal of the hair's natural oils and other conditioning and moisturizing components. The hair can further be left with increased levels of static upon drying, which can interfere with combing and result in a condition commonly referred to as "fly-away hair", or contribute to an undesirable phenomena of "split ends", particularly for long hair.

There remains a clear need for hair treatment compositions which are capable of imparting smoothness, moisturisation, ease of comb, etc, whilst also leaving the hair feeling clean, light and airy.

#### PRIOR ART

JP05/246,824 (Shiseido Co Ltd) discloses a hair cosmetic which is a water-in-oil emulsion containing an organically modified clay mineral (prepared by treating a water swelling clay with a nonionic surfactant and a cationic surfactant), a water-soluble high molecular weight substance and a high molecular weight silicone. The benefits claimed are smooth feel, lustre, firmness and flexibility to hair.

US 5786381 (Franklin et al) describes cosmetic compositions containing hydroxy materials, including layered double hydroxides for treating skin, which may be delivered from a shampoo. The hydroxide is combined with an anionic form of

- 3 -

a skin benefit agent which may be lactic acid, glycolic acid or alpha-hydroxycaprylic acid.

WO 02 19976 A (Procter and Gamble Co) describes hair conditioning compositions containing a high melting point fatty compound, a particle and a) an amidoamine and an acid or b) a cationic conditioning agent and a low melting point oil. The particle can be mica, silica, mud or clay. The benefit claimed is improved texture when spread on hands and/or hair.

EP 0726246 A (Rheox International) describes a quaternary ammonium composition comprising a blend of a liquid diluent and a quaternary ammonium compound. One suggested application is as reaction materials in the manufacture of organoclays.

It has now surprisingly been found that hair treatment compositions comprising an aqueous dispersion of composite particles, said composite particles comprising a clay with a net surface charge and a charged organic compound, said hair treatment composition further comprising one or more suitable hair treatment ingredients give benefits of smoothness, reduced friction, moisturisation and slippery feel whilst leaving the hair feeling clean, light and airy.

#### DEFINITION OF THE INVENTION

According to a first aspect of the invention, there is provided a hair treatment composition comprising an aqueous

- 4 -

dispersion of composite particles, said particles comprising:

- i) a clay with a net surface charge, and
- 5 ii) a charged organic molecule comprising at least 6, preferably at least 11, more preferably at least 17 carbon atoms,

wherein the charge on the charged organic molecule is  
10 opposite to the net surface charge of the clay, said hair treatment composition further comprising one or more suitable hair treatment ingredients.

According to a second aspect of the invention, there is  
15 provided a process for the preparation of composite particles, wherein the clay is mixed with the charged organic molecule, the clay preferably being added to an aqueous dispersion of the charged organic molecule.

20 According to a third aspect of the invention, there is provided a process for the preparation of a hair treatment composition comprising the steps of:

- (i) preparing an aqueous dispersion of composite particles, and
- 25 (ii) combining the aqueous dispersion of composite particles with suitable hair treatment ingredients in a compatible aqueous carrier.

DETAILED DESCRIPTION OF THE INVENTIONSuitable hair treatment compositions

5 Hair treatment compositions include such compositions as shampoo, conditioner, gel, mousse, shower gel, lotion and serum. Such compositions must be water based; by water based is meant that the composition contains at least 20, preferably 35, most preferably 50 percent water by weight of  
10 the total composition. Hair treatment compositions are suitably wash off compositions. Particularly preferred composition forms are shampoos and post-wash conditioners. For sake of clarity, water forms the continuous phase in compositions of the invention, which may be in the form of  
15 an emulsion or particulate dispersion.

The composite particles

The composite particles according to the invention provide  
20 feel benefits to hair when used in water based hair treatment compositions such as conditioner and shampoo compositions.

The composite particles essentially comprise a clay, which  
25 has a net charge on its layer surface, and a charged organic molecule.

In order to achieve good deposition onto hair, it is preferred if the particles according to the invention have a  
30 volume-based median particle diameter ( $D_{0.5}$ ) of greater than 1, preferably greater than 2, more preferably greater than 3

- 6 -

and most preferably greater than 4 microns, and in order to achieve a stable formulation, the particles suitably have a volume-based median particle diameter ( $D_{0.5}$ ) of less than 100, preferably less than 50, more preferably less than 19, more preferably less than 17 and most preferably less than 10 microns. For the sake of clarity, each upper limit can be combined with each lower limit to define suitable volume-based median particle diameter ranges. Volume-based median particle diameters can be determined using a Malvern Mastersizer (Malvern Instruments, UK).

The composite particles according to the invention are hydrophobic in character. The hydrophobicity is such that the particles can be dispersed in water to form an aqueous dispersion.

The said aqueous dispersion of composite particles is preferably substantially free from nonionic surfactant.

## 20 The clay

The clay which is used in the present invention can be any suitable clay material known in the art. In general, the term clay refers to a composition comprising fine particles which have a net electrostatic charge (i.e., positive or negative) on at least one surface. Preferably, the clay has a layered structure comprising sheets of coordinated cations, wherein the cations form tetrahedra or octahedra with close packed oxygens and hydroxyl groups. The surface charge is usually balanced by the presence of charge balancing ions (sometimes called exchangeable ions) which

- 7 -

are usually present between the layers of the clay and at the edges of the layers.

A suitable clay for the invention is an anionic clay. The  
5 term anionic clays and related terms, as used herein, refer to clays which are negatively charged at their layer surface. In this embodiment, the composite particles are formed with a cationic charged organic molecule, which is in addition to and separate from any charge balancing cations  
10 which may be present.

The clay may be a natural, synthetic or chemically modified clay. Preferably, the layers of the clay comprise hydrous sheets of octahedrally coordinated aluminium, magnesium or  
15 iron, or of tetrahedrally coordinated silicon. The arrangement of octahedrally coordinated cations to coordinating anions in the clay sheets may be dioctahedral or trioctahedral. The charge balancing ions are cations at the layer surfaces and anions at the edges and may be those  
20 occurring naturally in the clay or by exchange using ion exchange techniques. The charge balancing cations of the anionic clays employed in the composite particles of the invention will contain cationic counterions such as protons, sodium ions, potassium ions, calcium ions, magnesium ions,  
25 and the like.

Preferred anionic clays are 2:1 phyllosilicates, in which the clay layers comprise two tetrahedral sheets to one octahedral sheet. Preferred 2:1 phyllosilicates are  
30 smectite clays.



- 8 -

Other suitable clays have a 1:1 phyllosilicate structure, with an assemblage of one tetrahedral to one octahedral coordinated sheet in the clay layers.

- 5 Smectite clays, used in laundry compositions are, for example, disclosed in US Patents Nos 3,862,058, 3,948,790, 3,954,632 and 4,062,647 and in EP-A-299,575 and EP-A-313,146, all in the name of Procter & Gamble Company.
- 10 The term smectite clays herein includes both the clays in which aluminium oxide is present in a silicate lattice and the clays in which magnesium oxide is present in a silicate lattice. Typical smectite clay compounds include the compounds having the general formula  $\text{Al}_2(\text{Si}_2\text{O}_5)_2(\text{OH})_2 \cdot n\text{H}_2\text{O}$  and
- 15 the compounds having the general formula  $\text{Mg}_3(\text{Si}_2\text{O}_5)_2(\text{OH})_2 \cdot n\text{H}_2\text{O}$ , and derivatives thereof, for example in which a proportion of the aluminium ions are replaced with magnesium ions or a proportion of the magnesium ions are replaced with lithium ions and/or some of the hydroxyl
- 20 ions are replaced by fluoride ions; the derivatives may comprise a further metal ion to balance the overall charge.

- Specific examples of suitable smectite clays include those selected from the classes of the montmorillonites,
- 25 hectorites, volchonskoites, nontronites, saponites, beidelites and sauconites, particularly those having an alkali or alkaline earth metal ion within the crystal lattice structure. Particularly preferred are hectorites, montmorillonites, nontronites, saponites, beidelites,
- 30 sauconites and mixtures thereof. More preferably the clay is a synthetic hectorite.

- 9 -

The cation exchange capacity (CEC) of a clay is a well known parameter and may be determined by well established analytical techniques, including by electrodialysis, by exchange with ammonium ion followed by titration or by a methylene blue procedure, all as fully described in Grimshaw, "The Chemistry and Physics of Clays", pp. 264-265, Interscience (1971). It is customary to measure the cation exchange capacity of a clay in terms of milliequivalents per 100 g of dry clay (meq/100 g).

Preferred anionic clays for use in the present invention have a cation exchange capacity of from 0.7 meq/100 g to 150 meq/100 g. Particularly preferred are clays having a cation exchange capacity of from 30 meq/100 g to 100 meq/100 g.

The clays preferably have a volume-based median particle diameter ( $D_{0.5}$ ) from 0.001  $\mu\text{m}$  to 80  $\mu\text{m}$ , more preferably from 0.01  $\mu\text{m}$  to 50  $\mu\text{m}$  and most preferably 0.02  $\mu\text{m}$  to 20  $\mu\text{m}$ .

Particle diameters can be determined using a Malvern Mastersizer (Malvern Instruments, UK).

Examples of synthetic hectorites useful in the present invention include those products sold under the trade names Laponite RD, Laponite RDS, Laponite XLG, Laponite XLS, Laponite D, Laponite DF, Laponite DS, Laponite S and Laponite JS (all from Southern Clay products, Texas, USA, a subsidiary of Rockwood).

Examples of montmorillonites (also known as bentonites), which are suitable for use in the present invention include:

- 10 -

Gelwhite GP, Gelwhite H, Gelwhite L, Mineral Colloid BP, Mineral Colloid MO, Gelwhite MAS 100 (sc), Gelwhite MAS 101, Gelwhite MAS 102, Gelwhite MAS 103, Bentolite WH, Bentolite L10, Bentolite H, Bentolite L, Permont SX10A, Permont SC20, and Permont HN24 (Southern Clay Products, Texas, USA); Bentone EW and Bentone MA (Dow Corning); Bentonite USP BL 670 and Bentolite H4430 (Whitaker, Clarke & Daniels); Clarit 100 G1 and Clarit 1100 G1 (calcium bentonites from Süd Chemie AG); and Volclay 2 (sodium bentonite from Süd Chemie AG).

Clays may be used in the present invention either singly or in combination with one or more other clays. If a mixture of clays is used, however, it is preferred that either all of the clays are anionic or all of the clays are cationic. However, mixtures of cationic and anionic clays may be used.


Clays may be used as obtained from the supplier and may contain conventional additives such as, for example, disintegrating agents (also known as peptisers) and water of hydration. The clays may be used in their natural state or in a purified or semi-purified form, for example with the removal of mineral impurities.

Another suitable clay for the invention is a cationic clay. The term cationic clays and related terms, as used herein, refers to clays which are themselves cationic in nature i.e., the clays themselves are positively charged at their layer surfaces. In this embodiment, the composite particles are formed with an anionic charged organic molecule which is

- 11 -

in addition to and separate from any charge balancing anions which may be present in the clay.

Preferred examples of cationic clays are the natural or  
 5 synthetic layered double hydroxide (LDH) clays. For instance, layered double hydroxides include compounds of formula




10

where M is selected from divalent metal ions and lithium; N is a trivalent metal ion; X is an anion of charge x-; y+ is the net charge on the mixed metal hydroxide cation; and when M is a divalent metal ion, "a" is a number from 0.17 to 0.5  
 15 and y = a; and when M is lithium "a" is a number from 0.67 to 0.75 and y = (2a-1); and z is a number from 0 to 10.

In these structures, the metal ions occur in layers in which the metal ions are connected together through the OH groups  
 20 and the anions X, are located in interlayers between layers of metal ions. It is known that X can undergo ion exchange to be replaced by other anions e.g. organic anions. Various applications for these types of hydroxy materials have been described in the scientific literature, notably including  
 25 their use as chemical catalysts.

A preferred LDH is hydrotalcite, which has the formula:



30

- 12 -

Examples of cationic clays in the hydrotalcite category include Pural MG30, Pural MG50, Pural MG70 (from Condea Chemie GmbH, Hamburg, Germany). Hydrotalcites commercially available include Sorbacid EXM 911 and Hycite EM 713 (from 5 Süd Chemie AG). Other examples of layered double hydroxides are  $Mg_3Al_2(OH)_{12}(SO_4)_{0.8} \cdot xH_2O$  Magaldrate (Guilini) and  $Mg_4Al_4(OH)_{12}Cl_2 \cdot xH_2O$  mixed metal hydroxide (Dow Chemicals). Bayerite is also a suitable cationic clay.

- 10 Preferred cationic clays for use in the present invention have an ion exchange capacity of from 0.7 meq/100 g to 250 meq/100 g. Particularly preferred are clays having an ion exchange capacity of from 30 meq/100 g to 200 meq/100 g.
- 15 In the compositions of the invention, the clay is advantageously present in the form of a dispersion (for example a sol or gel) or a suspension of the clay particles.

#### The charged organic molecule

- 20 The charged organic molecule bears a charge which is opposite to that of the surface charge of the clay layer, and is derived from an organic ionic compound e.g. a salt. Any suitable charged organic species may be used. The charged
- 25 organic molecule may be cationic or anionic, depending on the charge type of the clay. Thus, a cationic charged organic molecule is used with an anionic clay and an anionic charged organic molecule is used with a cationic clay. The charged organic molecule can be a zwitterionic or an amphoteric
- 30 compound. For the sake of clarity, when such a zwitterionic

- 13 -

or amphoteric compound is used, the pH of the composition must be adjusted so as to achieve a charge on the zwitterionic or amphoteric compound, which is opposite to that of the surface charge of the clay layer. It will be well known to a person skilled in the art how to suitably adjust the pH of the composition so as to achieve a charge on the zwitterionic or amphoteric compound.

The charged organic molecule comprises an organic molecule with one or more charged substituents. By organic is meant any molecule containing carbon. The charged organic molecule comprises at least 6, preferably at least 11 and more preferably at least 17 carbon atoms. For the avoidance of doubt, the charged organic molecule is not the same as and is separate from the charge balancing ions, which are naturally present in the clay itself.

In order to form the composite particles, the charged organic molecule must be mixed with the clay. Suitably, the charged organic molecule will be added in the form of a neutral salt.

The charged organic molecule preferably contains at least one straight chain or branched alkyl group or carbon based chain, said alkyl group preferably comprises 3 to 22, more preferably 6 to 22 and most preferably 12 to 22 carbon atoms.

The charged organic molecule can also be a cationic or anionic, semi-permanent dye but preferably is not capable of imparting a colour to hair.

- 14 -

Positively charged organic molecules are preferably selected from the cations of cationic surfactants, cationic polymers and fatty amines used in combination with an acid; negatively charged organic molecules are preferably selected from the anions of anionic surfactants, anionic polymers and polyelectrolytes. For the sake of clarity, dyes are not included in these preferred subsets.

The weight ratio of the charged organic molecule to the clay is from 0.05:1 to 20:1, preferably from 0.1:1 to 10:1, and most preferably from 0.2:1 to 5:1. For the avoidance of doubt, the weight of the charged organic molecule mentioned in the above ratio refers to the weight of the charged organic molecule and excludes any counterion in the neutral salt from which the charged molecule may originate.

#### Cationic charged organic molecules


When an anionic clay is used, the charged organic molecule is preferably selected from the cation of a cationic surfactant, a cationic polymer and a fatty amine used in combination with an acid.

The preferred cationic charged organic molecule is the cation of a cationic surfactant.

Cationic surfactants useful in compositions of the invention contain amino or quaternary ammonium hydrophilic moieties which are positively charged in aqueous solutions.

- 15 -

Examples of suitable cationic surfactants are those corresponding to the general formula (I):



5

in which  $R_1$  and  $R_2$  are independently selected from (a) an aliphatic group of from 1 to 22, preferably 8 to 22, most preferably 16 to 22 carbon atoms, or (b) an aromatic, alkoxy, polyoxyalkylene, alkylamido, hydroxyalkyl, aryl or alkylaryl group having up to 22 carbon atoms;

10

$R_3$  and  $R_4$  are independently selected from (a) an aliphatic group of from 1 to 12, preferably 1 to 6, most preferably 1 to 3 carbon atoms, or (b) an aromatic, alkoxy, polyoxyalkylene, alkylamido, hydroxyalkyl, aryl or alkylaryl group having up to 12, preferably up to 6, most preferably up to 3 carbon atoms; and

15

$X$  is a salt-forming anion such as those selected from halogen, (e.g. chloride, bromide), acetate, citrate, lactate, glycolate, phosphate nitrate, sulphate, and alkylsulphate radicals.

20

The aliphatic groups can contain, in addition to carbon and hydrogen atoms, ether linkages, and other groups such as amino groups. The longer chain aliphatic groups, e.g., those of about 12 carbons, or higher, can be saturated or unsaturated.

25

Preferably,  $R_1$  of formula (I) is independently selected from (a) an aliphatic group of from 1 to 22, preferably 8 to 22, most preferably 16 to 22 carbon atoms, or

30



- 16 -

(b) an aromatic, alkoxy, polyoxyalkylene, alkylamido, hydroxyalkyl, aryl or alkylaryl group having up to 22 carbon atoms; and

R<sub>2</sub>, R<sub>3</sub> and R<sub>4</sub> and are independently selected from

- 5 (a) an aliphatic group of from 1 to 12, preferably 1 to 6, most preferably 1 to 3 carbon atoms, or
- (b) an aromatic, alkoxy, polyoxyalkylene, alkylamido, hydroxyalkyl, aryl or alkylaryl group having up to 12, preferably up to 6, most preferably up to 3 carbon
- 10 atoms; and

X is a salt forming anion.

More preferably, R<sub>1</sub> of formula (I) is C<sub>16</sub> to C<sub>22</sub> and R<sub>2</sub>, R<sub>3</sub> and R<sub>4</sub> are methyl groups.

15

Examples of suitable cationic surfactants include quaternary ammonium compounds, particularly quaternary ammonium compounds comprising a single straight or branched alkyl chain and three methyl groups in which said alkyl chain

20 comprises 16 to 22 carbon atoms.

Suitable quaternary ammonium compounds include cetyltrimethylammonium chloride (CTAC), behenyltrimethylammonium chloride (BTAC), cetylpyridinium

25 chloride, tetramethylammonium chloride, tetraethylammonium chloride, octyltrimethylammonium chloride, dodecyltrimethylammonium chloride, hexadecyltrimethylammonium chloride, octyldimethylbenzylammonium chloride, decyldimethylbenzylammonium chloride,

30 stearyldimethylbenzylammonium chloride,

- 17 -

tallowtrimethylammonium chloride, cocotrimethylammonium chloride, PEG-2 oleylammonium chloride, and salts of these, where the chloride is replaced by halogen, (e.g., bromide), acetate, citrate, lactate, glycolate, phosphate nitrate, sulphate, or alkylsulphate. Further suitable cationic surfactants include those materials having the CTFA designations Quaternium-5, Quaternium-31 and Quaternium-18.

Further suitable cationic surfactants include didodecyldimethylammonium chloride and dioctadecyldimethylammonium chloride.

Mixtures of any of the foregoing materials may also be suitable.

Preferred quaternary ammonium salts are behenyltrimethylammonium chloride (BTAC) such as Genamin KDMP supplied by Clariant and cetyltrimethylammonium chloride (CTAC), Such as Arquad 16/29 supplied by Akzo Nobel.

Further suitable cationic systems are primary, secondary, and tertiary fatty amines used in combination with an acid to provide the cationic species. The alkyl groups of such amines preferably have from 12 to 22 carbon atoms, and can be substituted or unsubstituted.

Particularly useful are amido substituted tertiary fatty amines, in particular tertiary amines having one C<sub>12</sub> to C<sub>22</sub>

- 18 -

alkyl or alkenyl chain. Such amines, useful herein, include stearamidopropyldimethylamine, stearamidopropyldiethylamine, stearamidoethyldiethylamine, stearamidoethyldimethylamine, palmitamidopropyldimethylamine, palmitamidopropyldiethylamine, palmitamidoethyldiethylamine, behenamidopropyldimethylamine, behenamidopropyldiethylamine, behenamidoethyldiethylamine, behenamidoethyldimethylamine, arachidamidopropyldimethylamine, arachidamidopropyldiethylamine, arachidamidoethyldiethylamine, arachidamidoethyldimethylamine, diethylaminoethylstearamide.

Also useful are dimethylstearamine, dimethylsoyamine, soyamine, myristylamine, tridecylamine, ethylstearylamine, N-tallowpropane diamine, ethoxylated (with 5 moles of ethylene oxide) stearylamine, dihydroxyethylstearylamine, and arachidyl behenylamine.

As stated previously, these amines are typically used in combination with an acid to provide the cationic species. The preferred acid useful herein includes L-glutamic acid, lactic acid, hydrochloric acid, malic acid, succinic acid, acetic acid, fumaric acid, tartaric acid, citric acid, L-glutamic hydrochloride, and mixtures thereof; more preferably L-glutamic acid, lactic acid, citric acid. Cationic amine surfactants included among those useful in the present invention are disclosed in U.S. Patent 4,275,055 to Nachtigal, et al., issued June 23, 1981.

The molar ratio of protonatable amines to  $H^+$  from the acid is preferably from about 1:0.3 to 1:1.2, and more preferably from about 1:0.5 to about 1:1.1.

- 5 Other suitable cationic charged organic molecules for use in the composite particles of the invention are cationic polymers.

These may be homopolymers or be formed from two or more types of monomers. The molecular weight of the polymer will generally be between 5,000 and 10,000,000, typically at least 10,000 and preferably from 100,000 to about 2,000,000 Da. The polymers will have cationic nitrogen containing groups such as quaternary ammonium or protonated amino groups, or a mixture thereof.

Suitable cationic nitrogen polymers are described in the CTFA Cosmetic Ingredient Directory, 3rd edition

The cationic polymers can comprise mixtures of monomer units derived from amine- and/or quaternary ammonium-substituted monomer and/or compatible spacer monomers.

Suitable cationic polymers include, copolymers of 1-vinyl-2-pyrrolidine and 1-vinyl-3-methyl-imidazolium salts (CTFA name Polyquaternium-16); copolymers of 1-vinyl-2-pyrrolidine and dimethylaminoethyl methacrylate, (CTFA name Polyquaternium-11); cationic diallyl quaternary ammonium-containing polymers in particular (CTFA Polyquaternium 6 and Polyquaternium 7, mineral acid salts of amino-alkyl esters of homo-and co-polymers of unsaturated carboxylic acids as

- 20 -

described in U.S. Patent 4,009,256; cationic polyacrylamides (as described in WO95/22311).

Cationic polysaccharide polymers suitable for use in compositions of the invention include those with an anhydroglucose residual group, such as a starch or cellulose. Cationic cellulose is available from Amerchol Corp. (Edison, NJ, USA) in their Polymer JR (trade mark) and LR (trade mark) series of polymers, as salts of hydroxyethyl cellulose reacted with trimethyl ammonium substituted epoxide, referred to in the industry (CTFA) as Polyquaternium 10. Another type of cationic cellulose includes the polymeric quaternary ammonium salts of hydroxyethyl cellulose reacted with lauryl dimethyl ammonium-substituted epoxide, referred to in the industry (CTFA) as Polyquaternium 24. These materials are available from Amerchol Corp. (Edison, NJ, USA) under the tradename Polymer LM-200.

Other suitable cationic polysaccharide polymers include quaternary nitrogen-containing cellulose ethers (e.g. as described in U.S. Patent 3,962,418), and copolymers of etherified cellulose and starch (e.g. as described in U.S. Patent 3,958,581).

A particularly suitable type of cationic polysaccharide polymer that can be used is a cationic guar gum derivative, such as guar hydroxypropyltrimonium chloride (commercially available from Rhodia in their JAGUAR trademark series). Particularly preferred cationic polymers are JAGUAR C13S,

- 21 -

JAGUAR C14, JAGUAR C15, JAGUAR C17 and JAGUAR C16 Jaguar CHT and JAGUAR C162.

Further suitable cationic charged organic molecules for use in the composite particles of the invention are cationic dyes. Suitable cationic dyes, which contain cationic charged organic molecules, include:

- 5 3-[(4-amino-6-bromo-5,8-dihydro-1-hydroxy-8-imino-5-oxo-2-naphthyl)amino]-N,N,N-trimethylanilinium chloride (CI 56059; Basic Blue No. 99- Trade name Arianor Steel Blue & Jaracol Steel Blue);
- 10 mixtures of: 8-[(4-amino-3-nitrophenyl)azo]-7-hydroxy-N,N,N-trimethyl-2-naphthaleneaminium chloride [Major]; 8-[(4-amino-2-nitrophenyl)azo]-7-hydroxy-N,N,N-trimethyl-2-naphthaleneaminium chloride [Minor] (Basic Brown No. 17 - Arianor Sienna Brown & Jaracol Sienna Brown);
- 15 8-[(4-aminophenyl)azo]-7-hydroxy-N,N,N-trimethyl-2-naphthaleneaminium chloride (CI 12250; Basic Brown No. 16 - Arianor Mahogany & Jaracol Mahogany);
- 3-[4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-N,N,N-trimethylanilinium chloride (CI 12719; Basic
- 20 Yellow No. 57 - Arianor Straw Yellow & Jaracol Straw Yellow); and
- 7-Hydroxy-8-[(2-methoxyphenyl)azo]-N,N,N-trimethyl-2-naphthaleneaminium chloride (CI 12245; Basic Red No. 76 - Arianor Madder Red & Jaracol Madder Red).

25

The dyes mentioned above are available from Warner Jenkinson Europe, Kings Lynn, Norfolk, UK. Jaracol dyes are available from James Robinson Dyes, Huddersfield, UK.

- 22 -

Other examples of suitable cationic dyes containing cationic charged organic molecules suitable for use in the invention include:

- 9-(dimethylamino)benzo[a]phenoxazin-7-ium chloride (CI 51175; Basic Blue No. 6);
- 5 di[4-(diethylamino)phenyl]-[4-(ethylamino)naphthyl]carbenium chloride (CI 42595; Basic Blue No. 7);
- 3,7-di-(dimethylaminophenothiazin-5-ium chloride (CI 52015; Basic Blue No. 9);
- 10 di[4-(dimethylamino)phenyl]-[4-(phenylamino)naphthyl]carbenium chloride (CI 44045; Basic Blue No. 26);
- 2[(4-(ethyl(2-hydroxyethyl)amino)phenyl)azo]-6-methoxy-3-methylbenzothiazolium methyl sulfate (CI 11154; Basic Blue
- 15 No. 41);
- bis[4-(dimethylamino)phenyl][4-(methylamino)phenyl]carbenium chloride (CI 42535; Basic Violet No. 1);
- tris-[4-(dimethylamino)phenyl]carbenium chloride (CI 42555; Basic Violet No. 3);
- 20 2-[3,6-(diethylamino)dibenzopyranium-9-yl]benzoic acid chloride (CI 45170; Basic Violet No. 10);
- di(4-aminophenyl)(4-amino-3-methylphenyl)carbenium chloride (CI 42510; Basic Violet No. 14);
- 1,3-bis[(2,4-diamino-5-methylphenyl)azo]-3-methylbenzene (CI
- 25 21010; Basic Brown No. 4);
- 1-[(4-amino-2-nitrophenyl)azo]-7-(trimethylammonio)-2-naphthol chloride (CI 12251; Basic Brown No. 17);
- 3,7-diamino-2,8-dimethyl-5-phenylphenazinium chloride (CI 50240; Basic Red No. 2);
- 30 1,4-dimethyl-5-[(4-(dimethylamino)phenyl)azo]-1,2,4-triazolium chloride (CI 11055; Basic Red No. 22);

2-[2-((2,4-dimethoxyphenyl)amino)ethenyl]-1,3,3-trimethyl-3H-indol-1-ium chloride (CI 48055; Basic Yellow No. 11); and bis[4-(diethylamino)phenyl]phenylcarbenium hydrogen sulfate (1:1) (CI 42040; Basic Green No. 1).

5

Charged organic molecules which are the cationic species in the so-called Basic dyes are particularly suitable.

#### Anionic charged organic molecules

- 10 The charged organic molecule is preferably selected from the anion of anionic surfactant, an anionic polymer and a polyelectrolyte, when a cationic clay is used.

- 15 The preferred anionic charged organic molecule is the anion of an anionic surfactant.

- Examples of suitable anionic surfactants are the alkyl sulphates, alkyl ether sulphates, alkaryl sulphonates, alkanoyl isethionates, alkyl succinates, alkyl
- 20 sulphosuccinates, alkyl phosphates, alkyl ether phosphates, alkyl carboxylates, alkyl ether carboxylates, alkyl ester carboxylates, N-alkyl sarcosinates, and alpha-olefin sulphonates, especially their sodium, magnesium, ammonium and mono-, di- and triethanolamine salts. The alkyl and acyl
- 25 groups generally contain from 8 to 22, preferably 12 to 22 carbon atoms, and may be saturated or unsaturated and can contain, in addition to carbon and hydrogen atoms, ether linkages, and other groups such as amino and ester groups. The alkyl ether sulphates, alkyl ether phosphates and alkyl



- 24 -

ether carboxylates may contain from 1 to 10 ethylene oxide or propylene oxide units per molecule.

Typical anionic surfactants for use in compositions of the invention include sodium oleyl sulpho succinate, ammonium lauryl sulphosuccinate, ammonium lauryl sulphate, sodium cocoyl isethionate, sodium lauryl isethionate and sodium N-lauryl sarcosinate, sodium lauryl sulphate, sodium lauryl ether sulphate(n)EO, (where n ranges from 1 to 3), ammonium lauryl sulphate, ammonium lauryl ether sulphate(n)EO, (where n ranges from 1 to 3), sodium heptadecyl sulphate, sodium and tetra decyl sulphate.

Further suitable anionic charged organic molecules are anionic polymers.

Examples of suitable anionic polymers are polyacrylates, cross-linked polyacrylates (for example Carbopol ETD 2001 supplied by Goodrich), hydrophobically modified polyacrylates (for example Carbopol 2623 supplied by Goodrich), polyalkylacrylates (for example Carbopol ETD 2020 supplied by Goodrich), polymethacrylates, polymethylvinylether/maleic anhydride (PVM/MA) copolymers (for example the Gantrez AN series supplied by ISP), alkyl esters of PVM/MA copolymers (for example, the Gantrez series supplied by ISP), monoester resins of PVM/MA copolymers (for example, the Gantrez ES series supplied by ISP), polymethylcarboxylates, polysulphonates and polyphosphates. Further suitable polymers are silicone glycol copolymers, such as DC Q2-5220 supplied by Dow Corning.

- 25 -

Further suitable anionic charged organic molecules for use in the composite particles of the invention are anionic dyes. Suitable anionic dyes, which contain anionic charged organic molecules, include azo dyes, xanthene dyes and dyes based on carbenium salts. Specific examples of dyes are:

5 6-hydroxy-5-[(4-sulfophenyl)azo]-2-naphthalenesulfonic acid disodium salt (CI 15985; Food Yellow No. 3);

2,4-dinitro-1-naphthol-7-sulfonic acid disodium salt (CI 10316; Acid Yellow No. 1; Food Yellow No. 1);

10 2-(2-quinolyl)-1H-indene-1,3(2H)-dione (mixture of mono- and disulfonic acid) (CI 47005; Food Yellow No. 13; Acid Yellow No. 3);

4,5-dihydro-5-oxo-1-(4-sulfophenyl)-4-[(4-sulfophenyl)azo]-1H-pyrazole-3-carboxylic acid trisodium salt (CI 19140; Food

15 Yellow No. 4; Acid Yellow No. 23);

3',6'-dihydroxyspiro[isobenzofuran-1(3H),9'-[9H]xanthen]-3-one disodium salt (CI 45350; Acid Yellow No. 73; D & C Yellow No. 8);

5-[(2,4-dinitrophenyl)amino]-2-phenylaminobenzenesulfonic

20 acid sodium salt (CI 10385; Acid Orange No. 3);

4-[(2,4-dihydroxyphenyl)azo]benzenesulfonic acid monosodium salt (CI 14270; Acid Orange No. 6);

4-[(2-hydroxy-1-naphthalenyl)azo]benzenesulfonic acid monosodium salt (CI 15510; Acid Orange No. 7);

25 4-[[3-[(2,4-dimethylphenyl)azo]-2,4-dihydroxyphenyl]azo]benzenesulfonic acid monosodium salt (CI 20170; Acid Orange No. 24);

4-hydroxy-3-[(4-sulfo-1-naphthalenyl)azo]-1-naphthalenesulfonic acid disodium salt (CI 14720; Acid Red

30 No. 14);

- 26 -

- 7-hydroxy-8-[(4-sulfo-1-naphthalenyl)azo]-1,3-naphthalenedisulfonic acid trisodium salt (CI 16255; Ponceau 4R; Acid Red No. 18);
- 3-hydroxy-4-[(4-sulfo-1-naphthalenyl)azo]-2,7-naphthalenedisulfonic acid trisodium salt (CI 16185; Acid Red No. 27; Food Red 9);
- 5-amino-4-hydroxy-3-(phenylazo)-2,7-naphthalenedisulfonic acid disodium salt (CI 17200; Acid Red No. 33);
- 5-(acetylamino)-4-hydroxy-3-[(2-methylphenyl)azo]-2,7-naphthalenedisulfonic acid disodium salt (CI 18065; Acid Red No. 35);
- 3'-6'-dihydroxy-2',4',5',7'-tetraiodospiro[isobenzofuran-1(3H),9'-[9H]xanthen]-3-one disodium salt (CI 45430; Acid Red No. 51);
- 15 N-[6-(diethylamino)-9-(2,4-disulfophenyl)-3H-xanthen-3-ylidene]-N-ethylethaneamminium hydroxide, internal salt, sodium salt (CI 45100; Acid Red No. 52);
- 7-hydroxy-8-[[4-(phenylazo)phenyl]azo]-1,3-naphthalenedisulfonic acid disodium salt (CI 27290; Acid Red No. 73);
- 20 2',4',5',7'-tetrabromo-3',6'-dihydroxyspiro[isobenzofurane-1(3H),9'-[9H]-xanthen]-3-one disodium salt (CI 45380; Acid Red No. 87);
- 2',4',5',7'-tetrabromo-4,5,6,7-tetrachloro-3',6',-dihydroxyspiro[isobenzofuran-1(3H),9'-[9H]-xanthen]-3-one disodium salt (CI 45410; Acid Red No. 92);
- 25 3',6'-dihydroxy-4'5'-diiodospiro[isobenzofuran]-1(3H),9'-(9H)-xanthen]-3-one disodium salt (CI 45425; Acid Red No. 95);
- 30

- 27 -

- Benzenemethanaminium, N-ethyl-N-[4-[[4-[ethyl[(3-sulfophenyl)methyl]amino]phenyl](2-sulfophenyl)methylene]2,5-cyclohexadiene-1-ylidene]-3-sulpho-, hydroxide, inner salt disodium salt, CI 42090; Acid
- 5 Blue No. 9);
- 2,2'-[(9,10-dihydro-9,10-dioxo-1,4-anthracenediyl)diimino]bis[5-methyl]benzenesulphonic acid disodium salt (CI 61570; Acid Green No. 25);
- 10 N-[4-[[4-(diethylamino)phenyl](2-hydroxy-3,6-disulfo-1-naphthalenyl)methylene]-2,5-cyclohexadien-1-ylidene]-N-methylmethanaminium hydroxide internal salt, monosodium salt (CI 44090; Food Green No. 4; Acid Green No. 50);
- 15 N-[4-[[4-(diethylamino)phenyl](2,4-disulfophenyl)methylene]-2,5-cyclohexadien-1-ylidene]-N-ethylethanaminium hydroxide internal salt, sodium salt (CI 42045; Food Blue No. 3; Acid Blue No. 1);
- 20 N-[4-[[4-(diethylamino)phenyl](5-hydroxy-2,4-disulfophenyl)methylene]2,5-cyclohexadien-1-ylidene]-N-ethylethanaminium hydroxide internal salt, calcium salt (2:1) (CI 42051; Acid Blue No. 3);
- 1-amino-4-(cyclohexylamino)-9,10-dihydro-9, 10-dioxo-2-anthracenesulfonic acid monosodium salt (CI 62045; Acid Blue No.62);
- 25 2-(1,3-dihydro-3-oxo-5-sulfo-2H-indol-2-ylidene)-2, 3-dihydro-3-oxo-1H-indole-5-sulfonic acid disodium salt (CI 73015, Acid Blue No. 74);
- 9-(2-carboxyphenyl)-3-[(2-methylphenyl)amino]-6-[(2-methyl-4-sulfophenyl)amino]xanthylum hydroxide internal salt, monosodium salt (CI 45190; Acid Violet No. 9);

- 28 -

- 2-[(9,10-dihydro-4-hydroxy-9,10-dioxo-1-anthracenyl)amino]-  
5-methylbenzenesulfonic acid monosodium salt (CI 60730; D & C  
Violet No. 2; Acid Violet No. 43);  
bis[3-nitro-4-[(4-phenylamino)-3-  
5 sulfophenylamino]phenyl]sulfone  
(CI 10410; Acid Brown No. 13);  
4-amino-5-hydroxy-3-[(4-nitrophenyl)azo]-6-(phenylazo)-2,7-  
naphthalenedisulfonic acid disodium salt (CI 20470; Acid  
Black No. 1);  
10 3-hydroxy-4-[(2-hydroxynaphth-1-yl)azo]-7-nitro-1-  
naphthalenesulfonic acid chromium complex (3:2) (CI 15711;  
Acid Black No. 52);  
3-[(2,4-dimethyl-5-sulfophenyl)azo]-4-hydroxy-1-  
naphthalenesulfonic acid disodium salt (CI 14700; Food Red  
15 No. 1; Ponceau SX; FD & C Red No. 4);  
4-(acetyl-amino)-5-hydroxy-6-[(7-sulfo-4-[(4-  
sulfophenyl)azo]-1-naphthalenyl)azo]-1,7-naphthalene  
disulfonic acid tetrasodium salt (CI 28440, Food Black No.  
1); and  
20 3-hydroxy-4-(3-methyl-5-oxo-1-phenyl-4, 5-dihydro- 1H-  
pyrazol-4-ylazo)naphthalene-1-sulfonic acid sodium salt,  
chromium complex (Acid Red No. 195).

Charged anionic organic molecules, which are the anionic  
25 species in the so-called Acid dyes are particularly  
preferred.

#### Further charged organic molecules

- 30 Further charged organic molecules are amphoteric or  
zwitterionic surfactants.

- 29 -

Examples of amphoteric and zwitterionic surfactants include, alkyl betaines, alkyl amidopropyl betaines, alkyl sulphobetaines (sultaines), alkyl glycinate, alkyl carboxyglycinates, alkyl amphopropionates, 5 alkylamphoglycinates, alkyl amidopropyl hydroxysultaines, acyl taurates and acyl glutamates, wherein the alkyl and acyl groups have from 8 to 19 carbon atoms. Typical amphoteric and zwitterionic surfactants for use in composite particles of the invention include lauryl amine oxide, cocodimethyl 10 sulphopropyl betaine and preferably lauryl betaine, cocamidopropyl betaine and sodium cocamphopropionate.

Preparation of the composite particles and hair treatment composition

15

The composite particles of the invention are prepared by mixing the charged organic molecule with the clay. The clay can be in a powdered form or as an aqueous suspension. The charged organic molecule is in the form of an aqueous 20 dispersion. The charged organic molecule can be added to the clay, or the clay can be added to the charged organic molecule to form an aqueous dispersion of composite particles.

25 The aqueous dispersion of composite particles can be used to prepare a hair treatment composition by combining with remaining suitable hair treatment ingredients in a compatible aqueous carrier. In said preparation of a hair treatment composition, the aqueous dispersion of composite 30 particles is prepared prior to addition to the remaining suitable hair treatment ingredients.

- 30 -

Hair treatment compositions in accordance with the invention are preferably formulated as products for the treatment of hair and subsequent rinsing.

5 Examples of hair treatment compositions that may be formed according to the present invention are a rinse off conditioner comprising a hair conditioning agent and a shampoo comprising a cleansing surfactant. By rinse off conditioner is meant a rinse off hair conditioner product,  
10 which is not a shampoo.

The weight of composite particles in the compositions of the invention is preferably from 0.01 to 20, more preferably 0.05 to 10 and most preferably 0.05 to 5 percent by weight  
15 of the total weight of the composition.

In a further aspect, the invention provides a method for treating hair, which comprises applying to the hair a hair treatment composition comprising an aqueous dispersion of  
20 composite particles.

In another aspect, the invention provides a method for modifying the feel of hair, which comprises applying to the hair a hair treatment composition comprising an aqueous  
25 dispersion of composite particles.

In another aspect, the invention provides a use of a hair treatment composition comprising an aqueous dispersion of composite particles to modify the feel of hair.

- 31 -

Hair Treatment Compositions

Compositions in accordance with the invention are preferably formulated as products for the treatment of hair and  
5 subsequent rinsing.

Shampoo Compositions

Shampoo compositions preferably comprise one or more  
10 cleansing surfactants which are cosmetically acceptable and suitable for topical application to the hair. Further surfactants may be present as emulsifiers.

Suitable cleansing surfactants, are selected from anionic,  
15 amphoteric and zwitterionic surfactants, and mixtures thereof. The cleansing surfactant may be the same surfactant as the emulsifier, or may be different.

Anionic Cleansing Surfactant

20 Shampoo compositions according to the invention will typically comprise one or more anionic cleansing surfactants which are cosmetically acceptable and suitable for topical application to the hair. These anionic surfactants may be  
25 the same as, but are additional to and separate from, the anionic surfactants which may be used to form part of the composite particles.

Examples of suitable anionic cleansing surfactants are the  
30 alkyl sulphates, alkyl ether sulphates, alkaryl sulphonates, alkanoyl isethionates, alkyl succinates, alkyl



- 32 -

sulphosuccinates, N-alkyl sarcosinates, alkyl phosphates, alkyl ether phosphates, alkyl ether carboxylates, alkyl ester carboxylates, and alpha-olefin sulphonates, especially their sodium, magnesium, ammonium and mono-, di- and

5 triethanolamine salts. The alkyl and acyl groups generally contain from 8 to 18 carbon atoms and may be unsaturated. The alkyl ether sulphates, alkyl ether phosphates and alkyl ether carboxylates may contain from 1 to 10 ethylene oxide or propylene oxide units per molecule.

10

Typical anionic cleansing surfactants for use in shampoo compositions of the invention include sodium oleyl sulpho succinate, ammonium lauryl sulphosuccinate, ammonium lauryl sulphate, sodium cocoyl isethionate, sodium lauryl

15 isethionate and sodium N-lauryl sarcosinate. The most preferred anionic surfactants are sodium lauryl sulphate, sodium lauryl ether sulphate(n)EO, (where n ranges from 1 to 3), ammonium lauryl sulphate and ammonium lauryl ether sulphate(n)EO, (where n ranges from 1 to 3).

20

The total weight of anionic cleansing surfactant in shampoo compositions of the invention is generally from 5 to 30, preferably from 6 to 20, more preferably from 8 to 16 percent by weight of the composition, excluding any anionic

25 surfactant which may be present in the composite particles.

#### Co-surfactant

The shampoo composition can optionally include co-

30 surfactants, preferably an amphoteric or zwitterionic surfactant, which can be included in an amount ranging from 0

- 33 -

to about 8, preferably from 1 to 4 percent by weight of the composition.

Examples of amphoteric and zwitterionic surfactants include, 5 alkyl betaines, alkyl amidopropyl betaines, alkyl sulphobetaines (sultaines), alkyl glycines, alkyl carboxyglycines, alkyl amphopropionates, alkylamphoglycines, alkyl amidopropyl hydroxysultaines, acyl taurates and acyl glutamates, wherein the alkyl and acyl 10 groups have from 8 to 19 carbon atoms. Typical amphoteric and zwitterionic surfactants for use in shampoos of the invention include lauryl amine oxide, cocodimethyl sulphopropyl betaine and preferably lauryl betaine, cocamidopropyl betaine and sodium cocamphopropionate.

15 Another preferred co-surfactant is a nonionic surfactant, which can be included in an amount ranging from 0 to 8, preferably from 2 to 5 percent, by weight of the composition.

20 For example, representative nonionic surfactants that can be included in shampoo compositions of the invention include condensation products of aliphatic ( $C_8 - C_{18}$ ) primary or secondary linear or branched chain alcohols or phenols with alkylene oxides, usually ethylene oxide and generally having 25 from 6 to 30 ethylene oxide groups.

Further nonionic surfactants which can be included in shampoo compositions of the invention are the alkyl polyglycosides (APGs). Typically, the APG is one which comprises an alkyl 30 group connected (optionally via a bridging group) to a block

- 34 -

of one or more glycosyl groups. Preferred APGs are defined by the following formula:



5

wherein R is a branched or straight chain C<sub>5</sub> to C<sub>20</sub> alkyl or alkenyl group, G is a saccharide group and n is from 1 to 10.

Other sugar-derived nonionic surfactants which can be included in shampoo compositions of the invention include the C<sub>10</sub>-C<sub>18</sub> N-alkyl (C<sub>1</sub>-C<sub>6</sub>) polyhydroxy fatty acid amides, such as the C<sub>12</sub>-C<sub>18</sub> N-methyl glucamides, as described for example in WO 92 06154 and US 5 194 639, and the N-alkoxy polyhydroxy fatty acid amides, such as C<sub>10</sub>-C<sub>18</sub> N-(3-methoxypropyl) glucamide.

15

The shampoo composition can also optionally include one or more cationic co-surfactants included in an amount ranging from 0.01 to 10, more preferably from 0.05 to 5, most preferably from 0.05 to 2 percent by weight of the composition. Useful cationic surfactants are described hereinbelow in relation to conditioner compositions.

20

The total weight of surfactant (including any co-surfactant, and/or any emulsifier, but excluding any surfactant which may be present in the composite particles) in shampoo compositions of the invention is generally from 5 to 50, preferably from 5 to 30, more preferably from 10 to 25 percent by weight of the composition.

25

- 35 -

Cationic Polymer

The shampoo composition can optionally include cationic polymer(s), which are separate from the cationic polymers which may be used to form part of the composite particles and which are described above. Suitable cationic polymers for use in shampoo compositions of the invention are the same as those described above.

The cationic polymer will generally be present in compositions of the invention at levels of from 0.01 to 5, preferably from 0.05 to 1, more preferably from 0.08 to 0.5 percent by weight of the composition, excluding any cationic polymer which may be present in the composite particles.

10 Conditioner CompositionsConditioning Surfactant

Conditioner compositions usually comprise one or more conditioning surfactants which are cosmetically acceptable and suitable for topical application to the hair.


Suitable conditioning surfactants are selected from cationic surfactants, used singly or in admixture. These cationic surfactants may be the same as, but are in addition to and separate from, the cationic surfactants which may be used to form part of the composite particles and which are described above.

- 36 -

Cationic surfactants useful in compositions of the invention contain amino or quaternary ammonium hydrophilic moieties which are positively charged when dissolved in the aqueous composition of the present invention.

5

Examples of suitable cationic surfactants are those corresponding to the general formula:



10

in which  $R_1$ ,  $R_2$ ,  $R_3$ , and  $R_4$  are independently selected from (a) an aliphatic group of from 1 to 22 carbon atoms, or (b) an aromatic, alkoxy, polyoxyalkylene, alkylamido, hydroxyalkyl, aryl or alkylaryl group having up to 22 carbon atoms; and X is a salt-forming anion such as those selected from halogen, (e.g. chloride, bromide), acetate, citrate, lactate, glycolate, phosphate nitrate, sulphate, and alkylsulphate radicals.

15

The aliphatic groups can contain, in addition to carbon and hydrogen atoms, ether linkages, and other groups such as amino groups. The longer chain aliphatic groups, e.g., those of about 12 carbons, or higher, can be saturated or unsaturated.

25

The most preferred cationic surfactants for conditioner compositions of the present invention are monoalkyl quaternary ammonium compounds in which the alkyl chain length is C16 to C22.

30

- 37 -

Examples of suitable cationic surfactants include quaternary ammonium compounds, particularly trimethyl quaternary compounds.

- 5 Preferred quaternary ammonium compounds include cetyltrimethylammonium chloride, behenyltrimethylammonium chloride (BTAC), cetylpyridinium chloride, tetramethylammonium chloride, tetraethylammonium chloride, octyltrimethylammonium chloride, dodecyltrimethylammonium
- 10 chloride, hexadecyltrimethylammonium chloride, octyldimethylbenzylammonium chloride, decyldimethylbenzylammonium chloride, stearyldimethylbenzylammonium chloride, didodecyldimethylammonium chloride,
- 15 dioctadecyldimethylammonium chloride, tallowtrimethylammonium chloride, cocotrimethylammonium chloride, PEG-2 oleylammonium chloride and salts of these, where the chloride is replaced by halogen, (e.g., bromide), acetate, citrate, lactate, glycolate, phosphate nitrate, sulphate, or alkylsulphate.
- 20 Further suitable cationic surfactants include those materials having the CTFA designations Quaternium-5, Quaternium-31 and Quaternium-18. Mixtures of any of the foregoing materials may also be suitable. Particularly useful quaternary ammonium cationic surfactants for use in hair conditioners of
- 25 the invention are cetyltrimethylammonium chloride, available commercially, for example as GENAMIN CTAC, ex Hoechst Celanese and Arquad 16/29 supplied by Akzo Nobel, and behenyltrimethylammonium chloride (BTAC) such as Genamin KDM-P supplied by Clariant. These may be the same as but are
- 30 in addition to and separate from any quaternary ammonium compounds that may be used as charged organic molecule.

- 38 -

Further suitable cationic systems are primary, secondary, and tertiary fatty amines used in combination with an acid to provide the cationic species. These are the same as but are in addition to and separate from any such amines and acids that may be used as charged organic molecule. The alkyl groups of such amines preferably have from 12 to 22 carbon atoms, and can be substituted or unsubstituted.

Particularly useful are amido substituted tertiary fatty amines, in particular tertiary amines having one C<sub>12</sub> to C<sub>22</sub> alkyl or alkenyl chain. Such amines, useful herein, include stearamidopropyldimethylamine, stearamidopropyldiethylamine, stearamidoethyldiethylamine, stearamidoethyldimethylamine, palmitamidopropyldimethylamine, palmitamidopropyldiethylamine, palmitamidoethyldiethylamine, palmitamidoethyldimethylamine, behenamidopropyldimethylamine, behenamidopropyldiethylamine, behenamidoethyldiethylamine, behenamidoethyldimethylamine, arachidamidopropyldimethylamine, arachidamidopropyldiethylamine, arachidamidoethyldiethylamine, arachidamidoethyldimethylamine, diethylaminoethylstearamide.

Also useful are dimethylstearamine, dimethylsoyamine, soyamine, myristylamine, tridecylamine, ethylstearylamine, N-tallowpropane diamine, ethoxylated (with 5 moles of ethylene oxide) stearylamine, dihydroxyethylstearylamine, and arachidyl behenylamine.

As stated previously, these amines are typically used in combination with an acid to provide the cationic species.

- 39 -

The preferred acid useful herein includes L- glutamic acid, lactic acid, hydrochloric acid, malic acid, succinic acid, acetic acid, fumaric acid, tartaric acid, citric acid, L-glutamic hydrochloride, and mixtures thereof; more preferably  
5 L-glutamic acid, lactic acid, citric acid. Cationic amine surfactants included among those useful in the present invention are disclosed in U.S. Patent 4,275,055 to Nachtigal, et al., issued June 23, 1981.

10 The molar ratio of protonatable amines to  $H^+$  from the acid is preferably from about 1:0.3 to 1:1.2, and more preferably from about 1:0.5 to about 1:1.1.

15 In the conditioners of the invention, the level of cationic surfactant is preferably from 0.01 to 10, more preferably 0.05 to 5, most preferably 0.1 to 2 percent by weight of the total composition, excluding any cationic surfactant which may be present in the composite particles.

20 Fatty Materials

Conditioner compositions of the invention preferably additionally comprise fatty materials. The combined use of fatty materials and cationic surfactants in conditioning  
25 compositions is believed to be especially advantageous, because this leads to the formation of a structured lamellar or liquid crystal phase, in which the cationic surfactant is dispersed.

30 By "fatty material" is meant a fatty alcohol, an alkoxylated fatty alcohol, a fatty acid or a mixture thereof.



- 40 -

Preferably, the alkyl chain of the fatty material is fully saturated.

Representative fatty materials comprise from 8 to 22 carbon atoms, more preferably 16 to 22. Examples of suitable fatty alcohols include cetyl alcohol, stearyl alcohol and mixtures thereof. The use of these materials is also advantageous in that they contribute to the overall conditioning properties of compositions of the invention.

Alkoxylated, (e.g. ethoxylated or propoxylated) fatty alcohols having from about 12 to about 18 carbon atoms in the alkyl chain can be used in place of, or in addition to, the fatty alcohols themselves. Suitable examples include ethylene glycol cetyl ether, polyoxyethylene (2) stearyl ether, polyoxyethylene (4) cetyl ether, and mixtures thereof.

The level of fatty material in conditioners of the invention is suitably from 0.01 to 15, preferably from 0.1 to 10, and more preferably from 0.1 to 5 percent by weight of the total composition. The weight ratio of cationic surfactant to fatty alcohol is suitably from 10:1 to 1:10, preferably from 4:1 to 1:8, optimally from 1:1 to 1:7, for example 1:3.

#### Optional Ingredients

#### Suspending Agents

In a preferred embodiment, the hair treatment composition, especially if it is a shampoo composition, further comprises

- 41 -

from 0.1 to 5 percent of a suspending agent, by weight of the total composition. Suitable suspending agents are selected from polyacrylic acids, cross-linked polymers of acrylic acid, copolymers of acrylic acid with a hydrophobic monomer, 5 copolymers of carboxylic acid-containing monomers and acrylic esters, cross-linked copolymers of acrylic acid and acrylate esters, heteropolysaccharide gums and crystalline long chain acyl derivatives. The long chain acyl derivative is desirably selected from ethylene glycol stearate, 10 alkanolamides of fatty acids having from 16 to 22 carbon atoms and mixtures thereof. Ethylene glycol distearate and polyethylene glycol 3 distearate are preferred long chain acyl derivatives. Polyacrylic acid is available commercially as Carbopol 420, Carbopol 488 or Carbopol 493. Polymers of 15 acrylic acid cross-linked with a polyfunctional agent may also be used, they are available commercially as Carbopol 910, Carbopol 934, Carbopol 941 and Carbopol 980. An example of a suitable copolymer of a carboxylic acid containing a monomer and acrylic acid esters is Carbopol 1342. All 20 Carbopol (trade mark) materials are available from Goodrich.

Suitable cross-linked polymers of acrylic acid and acrylate esters are Pemulen TR1 or Pemulen TR2. A suitable heteropolysaccharide gum is xanthan gum, for example that 25 available as Kelzan mu.

Conditioning AgentsSilicone Conditioning Agents

- 5 The compositions of the invention can contain, emulsified droplets of a silicone conditioning agent, for enhancing conditioning performance.

10 Suitable silicones include polydiorganosiloxanes, in particular polydimethylsiloxanes which have the CTFA designation dimethicone. Also suitable for use compositions of the invention (particularly shampoos and conditioners) are polydimethyl siloxanes having hydroxyl end groups, which have the CTFA designation dimethiconol. Also suitable for  
15 use in compositions of the invention are silicone gums having a slight degree of cross-linking, as are described for example in WO 96/31188.

20 The viscosity of the emulsified silicone itself (not the emulsion or the final hair conditioning composition) is typically at least  $10,000 \text{ mm}^2 \text{ s}^{-1}$  at  $25^\circ \text{C}$  the viscosity of the silicone itself is preferably at least  $60,000 \text{ mm}^2 \text{ s}^{-1}$ , most preferably at least  $500,000 \text{ mm}^2 \text{ s}^{-1}$ , ideally at least  $1,000,000 \text{ mm}^2 \text{ s}^{-1}$ . Suitable methods for measuring viscosity  
25 of viscous materials are given in "Corporate Test Method 004", Dow Corning Corporation, July 29, 1970.

Emulsified silicones for use in the shampoo compositions of the invention will typically have an average silicone  
30 droplet diameter in the composition of less than 30,

- 43 -

preferably less than 20, more preferably less than 10 microns, ideally from 0.01 to 1 microns. Silicone emulsions having volume-based median silicone droplet diameter ( $D_{0.5}$ ) of  $\leq 0.15$  microns are generally termed microemulsions.

5

Examples of suitable pre-formed emulsions include emulsions DC2-1766, DC2-1784, DC-1785 DC-1786 and microemulsions DC2-1865 and DC2-1870, all available from Dow Corning. These are all emulsions/microemulsions of dimethiconol. Cross-linked silicone gums are also available in a pre-emulsified form, which is advantageous for ease of formulation. A preferred example is the material available from Dow Corning as DC X2-1787, which is an emulsion of cross-linked dimethiconol gum. A further preferred example is the material available from Dow Corning as DC X2-1391, which is a microemulsion of cross-linked dimethiconol gum.

10

15

A further preferred class of silicones for inclusion in compositions of the invention are amino functional silicones. By "amino functional silicone" is meant a silicone containing at least one primary, secondary or tertiary amine group, or a quaternary ammonium group. Examples of suitable amino functional silicones include: polysiloxanes having the CTFA designation "amodimethicone".

20

25

Specific examples of amino functional silicones suitable for use in the invention are the aminosilicone oils DC2-8220, DC2-8166, DC2-8466, and DC2-8950-114 (all ex Dow Corning), and GE 1149-75, (ex General Electric Silicones).

- 44 -

Suitable quaternary silicone polymers are described in EP-A-0 530 974. A preferred quaternary silicone polymer is K3474, ex Goldschmidt.

5 Also suitable are emulsions of amino functional silicone oils with non ionic and/or cationic surfactant as emulsifiers. Pre-formed emulsions of amino functional silicone are also available from suppliers of silicone oils such as Dow Corning and General Electric. Specific examples  
10 include DC929 Cationic Emulsion, DC939 Cationic Emulsion, and the non-ionic emulsions DC2-7224, DC2-8467, DC2-8177 and DC2-8154 (all ex Dow Corning).

With shampoos it is particularly preferred to use a  
15 combination of amino and non amino functional silicones

The total weight of silicone is preferably from 0.01 to 10, more preferably from 0.3 to 5, most preferably 0.5 to 3 percent by weight of the total composition.

20

#### Non-silicone Oily Conditioning Components

Compositions according to the present invention may also comprise a dispersed, non-volatile, water-insoluble oily  
25 conditioning agent.

By "insoluble" is meant that the material is not soluble in water (distilled or equivalent) at a concentration of 0.1% (w/w), at 25°C..

30

- 45 -

Suitable oily or fatty materials are selected from hydrocarbon oils, fatty esters and mixtures thereof. Straight chain hydrocarbon oils will preferably contain from about 12 to about 30 carbon atoms. Also suitable are  
5 polymeric hydrocarbons of alkenyl monomers, such as C<sub>2</sub>-C<sub>6</sub> alkenyl monomers.

Specific examples of suitable hydrocarbon oils include paraffin oil, mineral oil, saturated and unsaturated  
10 dodecane, saturated and unsaturated tridecane, saturated and unsaturated tetradecane, saturated and unsaturated pentadecane, saturated and unsaturated hexadecane, and mixtures thereof. Branched-chain isomers of these compounds, as well as of higher chain length hydrocarbons,  
15 can also be used.

Specific examples of suitable mineral oils are preferably those having a low viscosity and/or low molecular weight, typically a molecular weight below 600 Da (eg, from 120 to  
20 600 Da) and/or a viscosity below 4 mm<sup>2</sup>s<sup>-1</sup>. Suitable methods for measuring viscosity of viscous materials are given in "Corporate Test Method 004", Dow Corning Corporation, July 29, 1970. For example, oils comprising straight chain or branched chain, saturated or unsaturated hydrocarbons having  
25 from 10 to 44 carbon atoms, optionally comprising one or more phenyl groups, are advantageously preferred.

Functionalised oils, preferably compounds containing one or more groups selected from ether, ester, keto, aldehyde,  
30 carboxyl, alcohol, diol, polyol, amino, amido, thiol,

- 46 -

thioether, and preferably containing 8 to 44 carbon atoms are suitable; specific examples are isoamyl ether, isopropyl myristate, octan-2-one, decyl alcohol and 1,10-decanediol; saccharide polyesters (eg, esters of sucrose with carboxylic acids having from 4 to 36 carbon atoms, such as sucrose pentaerucate).

Suitable fatty esters are characterised by having at least 10 carbon atoms, and include esters with hydrocarbyl chains derived from fatty acids or alcohols, monocarboxylic acid esters include esters of alcohols and/or acids of the formula  $R'COOR$  in which  $R'$  and  $R$  independently denote alkyl or alkenyl radicals and the sum of carbon atoms in  $R'$  and  $R$  is at least 10, preferably at least 20. Di- and trialkyl and alkenyl esters of carboxylic acids can also be used.

Particularly preferred fatty esters are mono-, di- and triglycerides, more specifically the mono-, di-, and triesters of glycerol and long chain carboxylic acids such as  $C_1$ - $C_{22}$  carboxylic acids. Preferred materials include cocoa butter, palm stearin, sunflower oil, soyabean oil and coconut oil.

The oily or fatty material is suitably present at a level of from 0.05 to 10, preferably from 0.2 to 5, more preferably from about 0.5 to 3 percent by weight of the composition.

- 47 -

EXAMPLES

The invention will now be further illustrated by the following, non-limiting Examples, in which parts and  
5 percentages are by weight.



Table A: Materials used in the examples.

Chemical	Active level	Trade Name	Supplier
Silicone emulsion (dimethicone)	60 %	DC1785	Dow Corning
Behenyltrimethyl ammonium chloride (BTAC)	85 %	*Genamin KDMP	Clariant
Cetearyl alcohol	100 %	*Laurex CS	Ellis & Everard
Methyl paraben	100 %	*Nipagen M	Chemlink Specialities
Synthetic clay (hectorite)	100 %	*Laponite XLS	Laporte
Quaternium 18 bentonite	100 %	*Tixogel MP100	Sud Chemie
Cetyltrimethyl ammonium chloride (CTAC)	29 %	Arquad 16/29	Akzo Nobel
Cocammonium carbanoyl chloride	40 %	Montaline C40	Seppic
Cationic guar	100 %	Jaguar CBS	Rhodia
Perfume	100 %	-	-
Sodium Lauryl Ether Sulphate (SLES)	28 %	Empicol ESB 28	Albright & Wilson
Cocoamidopropyl Betaine (CAPB)	30 %	Tegobetaine CK	Goldschmidt
Sodium Chloride	100 %	-	Aldrich

\* Trade Mark

- 49 -

Example 1 - Preparation of complexed clay particles

Complexed clay particles P1, P2, P3 and P4 were prepared from the raw materials shown in Table 1. The levels of raw materials are expressed as 100 % active.

Table 1:

Component	P1	P2	P3	P4	P5	P6
<b>charged organic molecule</b>						
CTAC	1.97	5.92	-	-	-	-
BTAC	-	-	1.97	5.92	-	-
cationic guar (Jaguar CBS)	-	-	-	-	1.97	-
Montaline C40	-	-	-	-	-	5.92
<b>clay</b>						
synthetic clay (hectorite)	3.95	11.85	3.95	11.85	3.95	11.85
<b>other</b>						
demineralised water	to 100	to 100	to 100	to 100	to 100	to 100

- 10 The charged organic molecule was added to the demineralised water and heated to 60°C with stirring (at speed setting 3-4 on a Silverson mixer, such as a Silverson L4R, ex-Silverson) for 30 minutes until it had dissolved. The resulting dispersion was allowed to cool to 30 to 35°C. The clay was
- 15 then added into the cooled dispersion in powder form and mixed for 15 minutes (at speed setting 3-4 on a Silverson mixer). The product obtained was a suspension of white particles in water.

- 50 -

Comparative Examples A, B and C

The following Comparative Examples (i.e. not according to the invention) were prepared as shown in Tables 2 to X

5 below:

Comparative Example A: basic hair conditioner.

Comparative Example B: hair conditioner containing synthetic clay (Laponite XLS).

10 Comparative Example C: hair conditioner containing commercially available hydrophobically modified clay (Quaternium 18 bentonite).

Comparative Examples A, B and C were prepared according to the formulations given in Table 2. The levels are expressed  
15 as 100 % active.

Table 2

Chemical name	weight %		
	A	B	C
silicone ex-emulsion DC1785	1.0	1.0	1.0
BTAC	2.0	2.0	2.0
cetearyl alcohol	4.0	4.0	4.0
methyl paraben	0.2	0.2	0.2
Perfume	0.6	0.6	0.6
Synthetic clay (hectorite)	-	0.67	-
Quaternium 18 bentonite	-	-	1.0
Demineralised water	to 100	to 100	to 100

- 51 -

Comparative example A was prepared by first heating the water to above 85 °C. The methyl paraben was then added with stirring using a Silverson mixer at speed 9-10, until it dissolved. The BTAC and Cetearyl alcohol were melted together and added to the aqueous methyl paraben solution under high shear (Silverson mixer at speed 9-10). The high shear was continued for 3 minutes and then allowed to cool to room temp under low shear (using a Heidolph mixer, such as a Heidolph RZ R2100). Silicone emulsion was then added with mixing.

Comparative Example B was prepared using the method described for Comparative Example A, but with the additional step of adding the synthetic clay (Laponite XLS), in powder form, at the end with the silicone, and mixing until dispersed throughout the conditioner.

Comparative Example C was prepared as follows:

The demineralised water was heated to above 85 °C and the methyl paraben added under high shear (Silverson mixer at speed 9-10) until it dissolved. The BTAC and Cetearyl alcohol were melted together and the Quaternium 18 bentonite dispersed into the melt. The resulting dispersion was then added to the aqueous methyl paraben solution under high shear. The high shear was continued for 3 minutes and the mixture was then allowed to cool to room temp under low shear. The silicone emulsion was then added with mixing.

- 52 -

Examples 2 to 7 - Hair conditioner compositions containing complexed clay particles

Conditioner compositions containing complexed clay particles  
5 were prepared by addition of the aqueous dispersions of  
composite particles (P1, P2, P3, P4, P5 or P6) to  
conditioner ingredients, to give the compositions shown in  
Table 3 below (Examples 2 to 7). Comparative example A (the  
conditioner formulation given in Table 2) is also shown,  
10 which contains no composite particles. Amounts are  
expressed as weight % of 100 % active ingredient, based on  
the weight of the total composition. The method of  
preparation of Examples 2 to 7 is given at the foot of Table  
3.

Table 3

	Example						
	2	3	4	5	6	7	A
<b>Conditioner</b>							
Silicone ex. DC1785	1.0	1.0	1.0	1.0	1.0	1.0	1.0
BTAC (I)	2.0	2.0	2.0	2.0	2.0	2.0	2.0
Cetearyl alcohol	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Methyl paraben	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Perfume	0.6	0.6	0.6	0.6	0.6	0.6	0.6
demineralised water (I)	75.41	75.41	75.41	75.41	75.41	75.41	92.2
complexed clay particles	P1	P2	P3	P4	P5	P6	-
CTAC	0.33	0.99	-	-	-	-	-
BTAC (II)	-	-	0.33	0.99	-	-	-
cationic polymer (Jaguar)	-	-	-	-	0.33	-	-
Montaline C40	-	-	-	-	-	0.99	-
synthetic clay (hectorite)	0.66	1.99	0.66	1.99	0.66	1.99	-
demineralised water (II)	15.8	13.81	15.8	13.81	15.8	13.81	-
total	100	100	100	100	100	100	100

The conditioner compositions containing complexed clay particles (Examples 2 to 7) were prepared as follows:

The demineralised water (I) was heated to above 85 °C and the methyl paraben added with stirring until it dissolved. The BTAC (I) and Cetearyl alcohol were melted together and added to the aqueous methyl paraben solution under high shear using a Silverson mixer at speed 9-10. The high shear was continued for 3 minutes and the suspension of composite particles (P1, P2, P3, P4, P5 or P6) was well shaken before being added under low shear (using a Heidolph mixer). The mixture was then allowed to cool to room temp under low shear. The silicone emulsion was then added with mixing.

- 54 -

Example 8 - Preparation of basic shampoo

A basic hair shampoo was prepared according to the formulation shown in Table 4. Weight percents are of the chemicals as 100% active and based on the weight of the total composition.

Table 4

Chemical name	Weight %
SLES	14.0
CAPB	2.0
demineralised water	82.5
sodium chloride	1.5
Total	100

The shampoo was prepared by mixing the ingredients together under medium shear (Silverson mixer at number 3-4).

Example 9 - Evaluation of hair friction

European dark brown hair was used in switches of 2.5 g weight and 6 inches length.

Each composition was tested on 5 such hair switches.

Friction measurement methodology

All friction measurements were carried out under controlled conditions of 20 °C and 50 % RH.

- 55 -

Friction was measured using a TA.XT2i Texture Analyser supplied by Stable Micro Systems, Surrey, UK. The friction probe was a stainless steel cylinder, which was coated with rubber material. The weight of the probe was approximately 5 60 g. When in use, an area of contact between the friction probe and the hair of approximately  $1.0 \text{ cm}^2$  was achieved.

The methodology used to assess the friction properties of hair treated with conditioner compositions was as follows:

10

A switch of hair was securely mounted onto the texture analyser, the hair fibres being aligned with combing before being secured. The friction probe was placed onto the hair and moved along the hair at a speed of  $10 \text{ mm s}^{-1}$  to measure 15 the friction between the probe and the hair. 2 measurements were performed per switch and 5 switches per composition were tested.

#### Treatment of hair with shampoo

20

Hair switches were first washed with the basic shampoo composition given in Table 4 above (which is not a shampoo according to the invention and as such contains no composite particles) according to the following protocol:

25

Each switch was first rinsed under running tap water for 30 seconds. Shampoo (0.5 ml) was applied to each switch and the hair agitated with gloved fingers for 30 seconds followed by further rinsing for 30 seconds under running tap

30

water.



- 56 -

The friction value of each wet switch was then measured using the texture analyser as described above. The switches were then dried at 50° C for 30 minutes and the friction re-measured using the texture analyser to obtain the dry friction value.

#### Treatment of hair with conditioners

Each hair switch, after the procedure above, was then treated with conditioner compositions as follows:

Each switch was first rinsed under running tap water for 10 seconds before conditioner (0.5 ml) was applied and massaged into the hair for 1 minute. The conditioner was then left on the hair for 1 minute without agitation before being rinsed under running tap water for 30 seconds. The texture analyser was then used to measure the friction of the wet switch. Again, following this measurement, the hair was dried at 50°C and the friction measured again to obtain the dry friction value.

The reduction in the friction of the shampooed hair as a result of treatment with the conditioner compositions was calculated as the difference in the friction value of each hair switch after shampooing and that of the hair switch after treatment with the conditioner compositions. This difference was then expressed as a percentage of the friction value of the shampooed hair. This calculation was performed for the wet and dry hair switches.

Two separate sets of experiments were performed:

- 57 -

Set 1) Examples 2 to 7 and Comparative Example A; wet and dry friction measured, and

Set 2) Example 2 and Comparative Examples A, B and C; wet friction measured.

5

Due to the nature of the experiments, results are only comparable within a single set of experiments and not between separate sets.

10 The percent reduction in friction thus calculated for the wet and dry hair switches treated with conditioner compositions (an average of 5 switches per composition) are shown in Tables 5 (Examples 2 to 7 and Comparative Example A) and 6 (Example 2 and Comparative Examples A, B and C)  
15 below.

Table 5

Example	% reduction in friction (wet)	% reduction in friction (dry)
A	50.4	25.5
2	64.2	43.2
3	60.1	41.3
4	54.4	28.1
5	55.4	32.4
6	57.1	24.5
7	53.5	34.1

20 It will be seen that both wet and dry friction of hair was dramatically reduced by use of the conditioner compositions

- 58 -

in accordance with the invention. In all cases, an additional benefit was seen over Comparative Example A.

5 Table 6

Example	% reduction in friction (wet)
A	57.2
B	50.9
C	59.2
2	65.3

It will be seen that wet friction of hair was dramatically reduced by use of the conditioner composition in accordance with the invention and an additional benefit was seen over Comparative Examples A, B and C.

Example 10 - Evaluation of hair feel by consumers

15 The hair used in the evaluation of hair feel was dark brown human hair in switches of approximately 11 inches in length and approximately 10 g in weight. Before use, the switches were balanced with respect to the feel attributes that were to be assessed, namely slippery feel, smooth feel and, 20 moisturised feel, such that there were no significant differences in these feel attributes between the switches.

The hair switches were cleaned prior to treatment with the conditioner compositions as follows: they were wetted with 25 running tap water for 10 s. The shampoo given in Table 4, which contains no composite particles, (0.14 g shampoo per g

- 59 -

hair) was dosed onto each switch and massaged for 30 s before being rinsed for 30 s.

Conditioner composition (0.14 g conditioner per g hair) was then applied to the washed, wet hair and massaged for 1 minute. The conditioner was left on the hair for 1 minute without agitation and rinsed under running tap water for 30 s. The switches were then allowed to dry. One switch per conditioner composition was used.

In this way, hair switches were treated with Examples 3 and 5 and Comparative Example A before being evaluated for slippery feel, smooth feel and moisturised feel by a panel of 10 consumers. The consumers used a sliding scale from 0 to 100 to evaluate each feel attribute for each composition.

The scores are shown in Table 7 below and are an average of the assessments by the 10 consumers.

Table 7

Example	Feel attribute		
	Slippery	Smooth	Moisturised
A	44.10	44.10	48.20
3	70.50	72.50	74.10
5	59.20	53.90	59.10

It will be seen that feel attributes are significantly increased on hair treated with conditioner compositions according to the invention, compared to hair treated with Comparative Example A.

- 60 -

CLAIMS

1. A hair treatment composition characterised in that it comprises an aqueous dispersion of composite particles,

5 wherein said particles comprise:

i) a clay with a net surface charge, and

ii) a charged organic molecule comprising at least 6, preferably at least 11, more preferably at least

10 17 carbon atoms,

wherein the charge on the charged organic molecule is opposite to the net surface charge of the clay, said hair

15 treatment composition further comprising one or more suitable hair treatment ingredients in a compatible aqueous carrier.

2. A composition as claimed in claim 1, wherein the particle size of the composite particles is from 1 to 100

20 microns, preferably 2 to 50 microns and most preferably 2 to 20 microns.

3. A composition as claimed in claim 1 or claim 2, wherein the weight ratio of the charged organic molecule to the clay

25 is from 0.05:1 to 20:1, preferably from 0.1:1 to 10:1, and most preferably from 0.2:1 to 5:1.

4. A composition as claimed in any preceding claim, wherein the clay has a net negative surface charge and the

30 charged organic molecule has a positive charge.

- 61 -

5. A composition as claimed in claim 4, wherein the clay is a synthetic hectorite.

6. A composition as claimed in claim 4 or claim 5, wherein the charged organic molecule is selected from the group consisting of the cation of a cationic surfactant, a cationic polymer and a fatty amine used in combination with an acid.

7. A composition as claimed in claim 6, wherein the charged organic molecule is the cation of an alkyl trimethyl ammonium chloride, wherein the alkyl chain comprises from 12 to 22 carbon atoms.

8. A composition as claimed in any one of claims 4 to 7, wherein the charged organic molecule is a cationic polymer.

9. A composition as claimed in claim 1, wherein the clay has a net positive surface charge and the charged organic molecule has a negative charge.

10. A composition as claimed in any preceding claim, wherein the charged organic molecule is not capable of imparting a colour to hair.

11. A composition as claimed in any preceding claim, wherein the composition is a rinse off hair conditioner.

12. A composition as claimed in any preceding claim, wherein the weight of composite particles, based on the total composition, is preferably from 0.01 to 20, more

- 62 -

preferably 0.05 to 10 and most preferably 0.05 to 5 percent by weight of the total composition.

13. A process for the preparation of composite particles as  
5 defined in any preceding claim, characterised in that the clay is mixed with the charged organic molecule, the clay preferably being added to an aqueous dispersion of the charged organic molecule.
- 10 14. A process for the preparation of a hair treatment composition according to any of claims 1 to 12 characterised in that it comprises the steps of:
- (i) preparing an aqueous dispersion of composite particles by the process of claim 13, and
  - 15 (ii) combining the aqueous dispersion of composite particles with the suitable hair treatment ingredients in a compatible aqueous carrier.
15. A method for treating hair, characterised in that it  
20 comprises applying to the hair a composition as claimed in any one of claims 1 to 12.
16. A method for modifying the feel of hair, characterised in that it comprises applying to the hair a composition as  
25 claimed in any one of claims 1 to 12.
17. Use of a hair treatment composition as claimed in any one of claims 1 to 12 characterised in that it modifies the feel of hair.

## INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/EP 02/0327A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 A61K7/13 A61K7/06

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data, CHEM ABS Data

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 823 250 A (SHISHEIDO COMPANY LIMITED) 11 February 1998 (1998-02-11) page 4, line 16 - line 26 page 4, line 4 - line 7; claim 1; examples 1-8, 1-9 examples 1-8 and 1-9 page 3, line 36 - line 43; claims 1,2	1-6, 12, 14, 15
X	DATABASE WPI Section Ch, Week 197926 Derwent Publications Ltd., London, GB; Class D21, AN 1979-48186B XP002197918 & JP 54 063132 A (SHISEIDO CO LTD), 21 May 1979 (1979-05-21) abstract	1, 9, 13

-/-

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \* & \* document member of the same patent family

Date of the actual completion of the international search

12 February 2003

Date of mailing of the international search report

04/03/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Pregetter, M



## INTERNATIONAL SEARCH REPORT

International Application No  
PCT/EP 02/12627

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 902 591 A (HERSTEIN MORRIS) 11 May 1999 (1999-05-11) column 3, line 24 - column 4, line 30; claims 1-6,9,10; examples 1,2	1-6,10, 12
X	US 5 968 491 A (RICHARDSON WENDY VICTORIA JANE) 19 October 1999 (1999-10-19)  column 2, line 27 - line 49 column 3, line 53 - line 67; claim 1; examples	1-7, 10-12, 14-17
X	US 4 390 033 A (KHALIL EZZAT N ET AL) 28 June 1983 (1983-06-28) column 2, line 45 - line 56 column 3, line 3 - line 44; claim 1; examples	1-7,10, 12,15-17
X	WO 99 25312 A (HOFMAN HANS ;MELBOUCI MOHAND (NL); DEBRUIN JACOBUS JOHANNES (NL);) 27 May 1999 (1999-05-27) page 6, line 5 - line 17 page 8, line 3 - line 12 page 9, line 1 - line 22; claims 1,16,19,33,51,61,62,66,67; examples 1,3-5	1-7, 10-17
X	US 5 112 603 A (LARYEA JOSEPH M ET AL) 12 May 1992 (1992-05-12) column 5, line 16 - line 22 column 6, line 15 - line 24 column 9, line 17 - line 24; claim 1; examples 1,2,11	1-6,8, 10,12-14
X	EP 0 099 987 A (HENKEL KGAA) 8 February 1984 (1984-02-08) page 4, line 4 - line 25; claims; examples page 9, line 18 - line 6 page 13, line 1 - line 15	1-3,9-17
X	DATABASE CA 'Online! CHEMICAL ABSTRACTS SERVICE, COLUMBUS, OHIO, US; MARKLAND, W. R.: "Laponite synthetic clays" retrieved from STN Database accession no. 80:124578 XP002230818 abstract & COSMETICS AND PERFUMERY (1974), 89(1), 24 ,	1,4-6,10

-/--

# INTERNATIONAL SEARCH REPORT

International Application No.

PCT/EP 02/00627

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 40 20 272 A (HENKEL KGAA)	13
A	2 January 1992 (1992-01-02) page 2, line 41 - line 55 page 3, line 22 - line 29 page 4, line 34 - line 35; claims 1,7,13; examples	1-12

## INTERNATIONAL SEARCH REPORT

Informative patent family members

International Application No

PCT/EP 02/0027

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0823250	A	11-02-1998	JP 10067624 A	10-03-1998
			EP 0823250 A2	11-02-1998
			JP 10101537 A	21-04-1998
			TW 434026 B	16-05-2001
			US 5817155 A	06-10-1998
JP 54063132	A	21-05-1979	JP 1390642 C	23-07-1987
			JP 61049349 B	29-10-1986
US 5902591	A	11-05-1999	EP 1037585 A1	27-09-2000
			JP 2002512604 T	23-04-2002
			WO 9843598 A2	08-10-1998
US 5968491	A	19-10-1999	CN 1166855 A	03-12-1997
			EP 0795003 A1	17-09-1997
			WO 9617050 A1	06-06-1996
US 4390033	A	28-06-1983	US 4237910 A	09-12-1980
			IT 1171625 B	10-06-1987
			CA 1146072 A1	10-05-1983
			GB 2058863 A , B	15-04-1981
WO 9925312	A	27-05-1999	AU 1416199 A	07-06-1999
			BG 104534 A	31-05-2001
			BR 9814693 A	03-10-2000
			CA 2311124 A1	27-05-1999
			CN 1285734 T	28-02-2001
			EP 1032358 A1	06-09-2000
			WO 9925312 A1	27-05-1999
			US 6113891 A	05-09-2000
US 5112603	A	12-05-1992	EP 0413783 A1	27-02-1991
			JP 4500522 T	30-01-1992
			WO 9007337 A1	12-07-1990
EP 0099987	A	08-02-1984	DE 3224585 A1	05-01-1984
			AT 21480 T	15-09-1986
			DE 3365446 D1	25-09-1986
			EP 0099987 A2	08-02-1984
DE 4020272	A	02-01-1992	DE 4020272 A1	02-01-1992
			WO 9200355 A1	09-01-1992

**THIS PAGE BLANK (USPTO)**